


SNAKE 1615T-TW

TECHNICAL SPECIFICATIONS



SVL Lighting



24V

IP67

IK08

- Vertical bending and Top lighting
- IP67 Tunable White LED Strip
- Dual color extrusion, diffused silicone lens and thermal conductive base
- UV and yellowing resistant
- Salt-mist proof
- L70 B50 > 50,000 hrs
- Extrusion and accessories are available
- Custom made length
- Ideal for commercial, hospitality and retail applications

Dimensions:	W: 16mm x H: 15mm
Max. Length	5m
Cutting Increment:	50mm
Voltage:	24VDC
Power:	9.6W/M
Trim Colour:	silicone
CRI:	>80/90
Colour Temp:	2700K-6000K
Power factor:	>0.9
Lumens	512lm/w
Beam Angle:	120°
Life Span:	up to 50,000 hrs

Controllers:

- Zigbee Remote Controller
- Touch Controller

* IES Files are available on request

Order Code	Wattage	Lumen	Colour Temp
SNAT9TW-1615	9.6w/m	512lm/w	2700K-6000K

* Please contact our sales team for specific requirements and order code




SVL Lighting

TECHNICAL SPECIFICATIONS


CONNECTORS:

- IP67 Power feed and end cap


Side feeder




Bottom feeder




End feeder



Bending Diagram



Correct bending direction and bending radius



Do not twist it or bending reversely

