

# LINO F-TW

## TECHNICAL SPECIFICATIONS




SVL Lighting



- Tuneable White Suspended /Surface Mounted LED Linear light (30x30mm)
- OSRAM PrevaLED Linear TW G2 Board and TW DRIVER
- The interlocking latch / pin system and continuous diffuser, give a Powder coat seamless finish
- Screwless interlocking end caps
- CSuspension kit provided
- Applications: hospitality, commercial, retail and residential
- Remote OSRAM TW DALI Dimmer available
- 560mm Board:  
2700K: 2152lm/w up to 6500K: 2287lm/w

<b>Model:</b>	Suspended/SM LED Linear
<b>Dimensions:</b>	30mm (W) x 30mm (H)
<b>Power :</b>	36w/mtr or Custom made
<b>Supply Voltage</b>	220-240VAC 50-60HZ
<b>Colour Temp:</b>	TW: 2700K-6500K
<b>Finish Colour:</b>	White/Black/Silver
<b>Initial Colour Consistency:</b>	3 SDCM
<b>CRI:</b>	>80/>90
<b>Power Factor:</b>	>0.95
<b>Lumens</b>	133 LM / W
<b>Dimmable:</b>	OSRAM TW-DALI

\* IES Files are available on request



L-module



T-module



X-module



- Please contact our sales team for specific requirements and Order Codes