TECHNICAL SPECIFICATIONS











IP20

- LED Spot track light completed with COB LED, Built in Driver
- 350° rotating and 180° Tilting
- Anti-dazzle design creates visual comfort
- Compact luminaire design to prevent the light emitting from backward.
- Suitable for 3-phase adapter
- Barn doors can be added as an extra to create theater style lighting distribution
- Application: Commercial, Retail stores, Hospitality

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
FOC2544B	25W	40°	4000K	В

^{*} Please contact our sales team for specific requirements and order code

45.	0 30.0 15.0 0.0 -15.0 -30.0	-45.0	
60.0	1/2×3/-1/2×2×	-60.0	
75.0		-75.0	
90.0		-90.0	
105.0		-105.0	
120.0		-120.0	
405.0	ノメルーレイン	-135.0	
135.0 150.0 165.0 -180.0 -165.0 -150.0 -135.0			
Polar Coordinates Curve			



Dimensions:	110mm X 246mm
Wattage:	25W, 30W, 37W
Finish Colour:	BLACK
CRI:	>90
Colour Temp:	3000K/4000K
Power Factor:	>0.95
Lumens	90lm/w
Beam Angle:	40°
Dimmable:	Osram PC, DALI-DIM
Life Span:	Up to 50,000 hrs

^{*}IES Files are available on request

