

ATHENA C WALL LIGHT







DESCRIPTION

- Recessed wall light
- Housing constructed in pressure die cast aluminium alloy
- Robust housing for superior protection
- Optimal thermal management guarantees a long lifespan
- Anti-dazzle design creates visual comfort
- Special structure with matt glass makes smooth light distribution.
- Suitable for a pre-embedded box in the wall, easy to install.

APPLICATION

external walls of the building, porches, hallways, corridors, and stairways

Code	Wattage	CRI	Colour Temp	Colour
ATHC33B	3W	83	3000K	Black

TECHNICAL SPECIFICATION

Model	ATHENA C LED Wall Light		
Dimensions	W:220mm H:85mm D: 79mm		
Finish Colour	Black		
Colour Temp	3000K		
IP Rating	IP65		
CRI	83		
Beam Angle	85°		
Cut out Size			
Power Consumption	3W		
Power Factor	> 0.90		
Lumen of Lumenarie	300lm		
Dimmable			
Life time	Up to 50,000 hrs		

INSTALLATION HOUSING (use these for all Athena series)














ousing: Plastic. Available accessories AC-UD104E.


AC-104S Housing: stainless Steel 304.

Mounting instruction for wooden wall












2 | [Type text]

Mounting instruction for concrete wall (with AC-104)



.....

PHOTOMETRIC

IES files are available on request