

# LINO A suspended



## TECHNICAL SPECIFICATIONS



## OSRAM

## IP40

- Architecturally designed LED linear light (69 x 80)
- OSRAM LED Board and DRIVER
- The interlocking latch / pin system and continuous diffuser, give a Powder coat seamless finish
- Screwless interlocking end caps
- Can be custom made according to client's request
- Reflector and diffuser are designed to provide even light distribution
- Suspension kit provided
- Applications: hospitality, commercial, retail and residential

<b>Model:</b>	Suspended LED Linear
<b>Dimensions:</b>	69mm (W) x 80mm (H)
<b>Power:</b>	36w/lm or custom made
<b>Lumens</b>	122 LM/W
<b>Colour Temp:</b>	3000K/4000K
<b>Finish Colour:</b>	White/Black/Silver Custom Powder Coat
<b>CRI:</b>	>90
<b>Power Factor:</b>	>0.95
<b>Accessories:</b>	EMERGENCY Kit, Sensors, Joints
<b>Dimmable:</b>	Trailing edge, 1-10V, DALI Tuneable White
<b>Life Span:</b>	50,000 hrs

Order Code	Wattage	Length	Colour Temp	Trim color
LINA363W	36W	1160mm	3000K	W
LINA724B	72W	2254mm	4000K	B

- Please contact our sales team for specific requirements and all other item codes

\* IES Files are available on request

### L-module



### T-module



### X-module

