


SQIN A-TW Tunable White



SVL Lighting

TECHNICAL SPECIFICATIONS



OSRAM



IP40

- Recessed Square adjustable downlight
- Recessed black housing creating a dynamic visual impact with low glare
- OSRAM OT Phase-cut tuneable driver (PC TW)
- OSRAM PrevaLED COIN 50 DC COB TW
- Targeting Human Centric Lighting (HCL)
- High flux output up to 1,000lm
- Gimble and rotatable ring gives directional flexibility for both ambient and feature lighting
- Ideal for applications in foyers, hotels, corridors, function rooms, living area, kitchens
- 5 years warranty on LED

Trim Dimensions:	175mm x 175mm
Cut out:	160mm x 160mm
Power:	10.1W
Finish Colour:	White /Black /Silver
CRI:	90
Wide CCT:	2700K - 6500K
Power Factor:	>0.9
Lumens	910lm – 1020lm @ 40° 865lm – 970lm @ 24°
Beam Angle:	24°, 40°
Dimmable:	OT phase-cut TW DIM Driver
Life Span:	50,000 Hrs



* IES Files are available on request

Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
SENSQTW40W	10.1W	40D	2700-6500K	W
SENSQTW24W	10.1W	24D	2700-6500K	W