

SQIN B-TW Tunable White



SVL Lighting

TECHNICAL SPECIFICATIONS




OSRAM



- Twin square downlight solution to replace CFL and metal halide lighting
- Ideal for applications in hospitality, retail and commercial
- Available with surface mounted case
- OSRAM OT Phase-cut tunable driver (PC TW)
- OSRAM PrevaLED COIN 50 DC COB TW
- Targeting Human Centric Lighting (HCL)
- High flux output up to 1,000 lm
- 5 years warranty on LED

Dimensions:	315mm x 175mm x D206mm
Cut out:	295mm x 160mm
Power Consumption:	2x10.1W
Finish Colour:	White, Silver, Black
CRI:	80/90
Colour Temp:	2700K - 6500K
Power Factor:	>0.95
Lumens	2 x 910-1020lm @40° 2 x 865lm-970lm @ 24°
Beam Angle:	24°, 40°
Dimmable:	OT phase-cut tunable white 10W driver (PC TW)
Life Span:	50,000 Hrs

* IES Files are available on request



Order Code	Wattage	Beam Angle	Colour Temp	Trim colour
SQIBTW103W	2x10.1W	40°	2700 -6500K	W/S/B
SQIBTW102W	2x10.1W	24°	2700 -6500K	W/S/B