


TECHNICAL SPECIFICATIONS



OSRAM

IP40

- Architecturally designed Slim LED linear light (50 x 50) with two installation options: **Surface mount and Suspended.**
- OSRAM LED Board and DRIVER
- The interlocking latch / pin system and continuous diffuser, give a powder coated seamless finish
- Reflector and diffuser are designed to provide even light distribution
- Screwless interlocking end caps
- Can be custom made according to client's request
- Applications: hospitality, commercial, retail and residential

Model:	Suspended /SM Slim LED Linear
Dimensions:	50mm (W) x 50mm (H)
Power Consumption:	36w/54w/72w Custom made
Lumens	122 LM/W
Colour Temp:	3000K/4000K
Finish Colour:	White/Black/Silver Custom Powder Coat
CRI:	>90
Power Factor:	>0.95
Accessories:	EMERGENCY Kit, Sensors, Joints
Dimmable:	Trailing edge, 1-10V, DALI Tuneable White
Life Span:	50,000 hrs

* IES Files are available on request

Order Code	Wattage	Length	Colour Temp	Trim Color
LINE363W	36W	1160mm	3000K	W
LINE544B	54W	1700mm	4000K	B
LINE723S	72W	2260mm	3000K	S

- Please contact our sales team for specific requirements and all other item codes

- Suspension Wire Kit available

